


Blue Discharge Hose

Size	Maximum Pressure	Weight Per Foot	Width Laying Flat	Approx Wall Thickness
1 1/2"	80 psi	.17 lbs	2 1/2"	0.055"
2"	80 psi	.23 lbs	3 1/8"	0.060"
3"	70 psi	.40 lbs	4 11/16"	0.063"
4"	70 psi	.52 lbs	6 1/4"	0.063"
6"	50 psi	.85 lbs	9 3/8"	0.071"

Features

- 30 Day warranty
- Male coupling - Aluminum (NPT)
- Female coupling - Brass (NPSH)
- Tube - Blue lay flat PVC
- Galvanized band clamps
- Type of use - Water
- Outside temperature - 150° F to 14° F





Warning - Not intended for indoor use, fire fighting or closed pressure applications such as use with nozzles. Used for open ended discharge applications only.

Hose is not rated for air or any other liquids. Test ratings are for water use only with discharge couplings installed.



WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer/birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Agriculture



Residential



Pump Discharge



Light Industrial

Any hose found to be defective due to materials and / or workmanship shall be replaced at no charge up to 30 days. In general, hose warranties cover manufacturing defects leading to hose failure. Wear through and abuse are not covered by warranty.