

Double Jacket Mill Hose

Size	Service Test	Burst Test	Weight Per Foot Uncoupled	Width Laying Flat	Bowl Size
1"	150 psi	450 psi	.16 lbs	1 3/4"	1 3/8"
1 1/2"	150 psi	450 psi	.20 lbs	2 5/8"	1 13/16"
2"	150 psi	450 psi	.28 lbs	3 1/2"	2 5/16"
2 1/2"	150 psi	450 psi	.37 lbs	4 3/8"	2 13/16"
3"	150 psi	450 psi	.60 lbs	5 1/16"	3 3/8"
4"	150 psi	450 psi	.83 lbs	6 1/4"	4 3/8"

Features

- 30 Day warranty
- Mildew resistant
- Polyester double jacket
- Liner - Synthetic SBR Rubber
- Every hose is tested





Test Ratings (Water Only With Expansion Ring Couplings)

- Service Pressure
(A 3-minute hydrostatic test conducted by users on in-service hose to determine suitability for continued service)
- PSI Burst Test Pressure

Warning - Hose is not rated for air or any other liquids. Test ratings are for water use only with expansion ring couplings installed. Internal temperature of water not to exceed 103° F.



WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer/birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Light & Medium Industrial



Residential

Any hose found to be defective due to materials and / or workmanship shall be replaced at no charge up to 30 days. In general, hose warranties cover manufacturing defects leading to hose failure. Wear through and abuse are not covered by warranty.