

Double Jacket Camlock Hose

Size	Service Test	Burst Test	Weight Per Foot Uncoupled	Width Laying Flat	Bowl Size
1 1/2"	150 psi	450 psi	.20 lbs	2 5/8"	1 13/16"
2"	150 psi	450 psi	.28 lbs	3 1/2"	2 5/16"
2 1/2"	150 psi	450 psi	.37 lbs	4 3/8"	2 13/16"
3"	150 psi	450 psi	.60 lbs	5 1/16"	3 3/8"
4"	150 psi	450 psi	.83 lbs	6 1/4"	4 3/8"

Features

- 30 Day Warranty
- Female aluminum camlock fitting
- Male aluminum camlock fitting
- Tube - Black Lay Flat EPDM Rubber Liner
- Type of Use - Water
- Double Jacket
- 100% All Polyester
- Galvanized band clamps





Warning - Hose is not rated for air or any other liquids.

Test ratings are for water use only with Camlock couplings installed. Internal temperature of water not to exceed 103° F. Not intended for fire fighting.



WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer/birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Heavy Industrial



Agricultural Hose

Any hose found to be defective due to materials and / or workmanship shall be replaced at no charge up to 30 days. In general, hose warranties cover manufacturing defects leading to hose failure. Wear through and abuse are not covered by warranty.