

# Potable Water Hose



Size	Service Test	Proof Test	Burst Test	Weight Per Foot Uncoupled	Width Laying Flat	Bowl Size
1 1/2"	400 psi	800 psi	1200 psi	.31 lbs	2 3/4"	1 15/16"
2 1/2"	400 psi	800 psi	1200 psi	.52 lbs	4 3/8"	3"

## Features

- Proudly made in the U.S.A.
- 5 Year warranty
- Male coupling - Brass NH / NST or NPSH
- Swivel female coupling - Brass NH / NST or NPSH
- Polyester double jacket (mildew resistant)
- Color - Blue
- Polyurethane liner NSF-61 compliance
- Meets or exceeds Mil-H-24606B
- Features NSF-61 approved polyurethane hose lining for potable water





## Test Ratings (Water Only With Expansion Ring Couplings)

- Service Pressure  
*(A 3-minute hydrostatic test conducted by users on in-service hose to determine suitability for continued service)*
- Proof Test Pressure *(A pressure equal to a least two times the service test pressure)*
- PSI Burst Test Pressure



**Warning - Hose is not rated for air or any other liquids. Test ratings are for water use only with expansion ring couplings installed. Internal temperature of water not to exceed 103° F.**



**Any hose found to be defective due to materials and / or workmanship shall be replaced at no charge up to five years. In general, hose warranties cover manufacturing defects leading to hose failure. Wear through and abuse are not covered by warranty.**

# Potable Water Hose



Size	Maximum Pressure	Weight Per Foot	Width Laying Flat
1"	150 psi	.11 lbs	1 1/2"

## Features

- 1 Year warranty
- Male coupling - Brass garden hose threads (GHT)
- Swivel female coupling - Brass garden hose threads (GHT)
- Galvanized band clamps
- Color - Blue
- Extruded hose through the weave construction textile
- Circular woven high tenacity polyester
- Inner and outer layer - polyurethane (PU)
- With a strip of reinforced polyurethane
- Certified for drinking water under the NSF-61 standards



**Warning - Hose is not rated for air or any other liquids. Test ratings are for water use only with expansion ring couplings installed. Internal temperature of water not to exceed 103° F.**



**Any hose found to be defective due to materials and / or workmanship shall be replaced at no charge up to one year. In general, hose warranties cover manufacturing defects leading to hose failure. Wear through and abuse are not covered by warranty.**