

# Large Diameter Supply Hose

## Industrial Fire Hose

Size	Service Test	Proof Test	Burst Test	Weight Per Foot Uncoupled	Width Laying Flat
5"	200 psi	400 psi	600 psi	.93 lbs	7 3/4"

### Features

- 1 Years warranty
- Heat and chemical resistant
- Couplings - Locking aluminum storz
- Nitrile / PVC Through-The-Weave
- Maintenance free
- Thin rib construction to aid abrasion resistance
- All weather performance to -36°F
- Available in 25, 50, 100 feet



### Test Ratings (Water Only With Expansion Ring Couplings)

- Service Pressure  
*(A 3-minute hydrostatic test conducted by users on in-service hose to determine suitability for continued service)*
- Proof Test Pressure *(A pressure equal to a least two times the service test pressure)*
- PSI Burst Test Pressure





**Warning - Hose is not rated for air or any other liquids. Test ratings are for water use only with Storz couplings installed. Internal temperature of water not to exceed 103° F.**

**Nitrile/PVC**  
Through-The-Weave

**Synthetic**  
Polyester Yarn

**Nitrile/PVC**  
Through-The-Weave



Supply



Power Plant



Heavy Industrial

**Any hose found to be defective due to materials and / or workmanship shall be replaced at no charge up to five years. In general, hose warranties cover manufacturing defects leading to hose failure. Wear through and abuse are not covered by warranty.**