

Pin Rack Hose

Size	Service Test	Proof Test
1 1/2"	250 psi	500 psi
2 1/2"	250 psi	500 psi

Features

- 30 Day Warranty
- Male Coupling - Brass NH
- Swivel Female Coupling - Brass NH
- Polyester Single Jacket (Mildew Resistant)
- Color - White
- Liner - Polyurethane
- Pre-folded for ease of installation
- FM Approved Standard
- Designed for Interior Fire Fighting ONLY
- Each Hose is Dated Prior to Shipment
- Number of Folds (Approximately)
 - 50' – 12 folds
 - 75' – 19 folds
 - 100' – 25 folds
 - 125' – 27 folds



Test Ratings (Water Only With Expansion Ring Couplings)

- Service Pressure
(A 3-minute hydrostatic test conducted by users on in-service hose to determine suitability for continued service)
- Proof Test Pressure *(A pressure equal to a least two times the service test pressure)*



Warning - Hose is not rated for air or any other liquids. Test ratings are for water use only with expansion ring couplings installed. Designed for one time use.



Interior Fire
Fighting



Office
Buildings



Underwriter
Laboratories

Any hose found to be defective due to materials and / or workmanship shall be replaced at no charge up to 30 days. In general, hose warranties cover manufacturing defects leading to hose failure. Wear through and abuse are not covered by warranty.