

USCG Single Jacket Hose



Size	Service Test	Proof Test	Burst Test	Weight Per Foot Uncoupled	Width Laying Flat	Bowl Size
1 1/2"	250 psi	500 psi	750 psi	.15 lbs	2 7/16"	1 3/4"
2 1/2"	300 psi	600 psi	900 psi	.33 lbs	3 3/16"	2 3/4"

Features



- Proudly made in the U.S.A.
- 1 Year warranty
- Male coupling - Brass NH / NST or NPSH
- Swivel female coupling - Brass NH / NST or NPSH
- Polyester single jacket (mildew resistant)
- Color - White
- Liner - EPDM rubber
- ZZ-H-451-G Compliant
- Meets and exceeds all NFPA 1961 standards
- Brass couplings
- All hoses dated
- All hoses stenciled UL19



Test Ratings (Water Only With Expansion Ring Couplings)

- Service Pressure
(A 3-minute hydrostatic test conducted by users on in-service hose to determine suitability for continued service)
- Proof Test Pressure *(A pressure equal to a least two times the service test pressure)*
- PSI Burst Test Pressure

Warning - Hose is not rated for air or any other liquids. Test ratings are for water use only with expansion ring couplings installed. Internal temperature of water not to exceed 103° F.



Any hose found to be defective due to materials and / or workmanship shall be replaced at no charge up to one year. In general, hose warranties cover manufacturing defects leading to hose failure. Wear through and abuse are not covered by warranty.